



Product Fiche

| | |
|--|---------------|
| Model number | TL48W.E |
| TECHNICAL DATA | |
| Power supply voltage | 220-240V |
| Frequency (Hz) | 50 |
| Refrigerant | R600a |
| Current of product (A) | 0.8 |
| Total gross volume (l) | 47 |
| Total net volume (l) | 49 |
| Freezer net volume (l) | 0 |
| Refrigerator net volume (incl. fresh food comp.) (l) | 47 |
| Fresh Food Compartment Net Volume (l) | / |
| Freezing capacity (kg/24h) | / |
| Max storage time in freezer by power failure (h) | / |
| PRODUCT PARAMETERS | |
| Low-noise appliance | No |
| Design type | Free Standing |
| Wine storage appliance | No |
| Other refrigerating appliance | |
| Total volume | 49 |
| Energy efficiency class | F |
| Energy efficiency index (EEI) | 124.5 |
| Annual energy consumption (AE) | 100.38 |
| Standard annual energy consumption (SAE) | 80.64 |
| Auxiliary energy (Eaux) | 0.000 |
| Daily energy consumption at 16°C (E16) | 0.130 |
| Daily energy consumption at 32°C (E32) | 0.420 |
| Incremental defrost and recovery energy consumption at 16°C (ΔE_{d-f16}) | 0.000 |
| Incremental defrost and recovery energy consumption at 32°C (ΔE_{d-f32}) | 0.000 |
| Defrost interval at 16°C (td-f16) | 0.0 |

| | |
|---|-------------|
| Defrost interval at 32°C (td-f32) | 0.0 |
| Temperature rise time | / |
| Combi parameter | 1.000 |
| Door heat loss factor (D) | / |
| Load factor (L) | |
| Anti-condensation heater type | |
| Climate class | subtropical |
| Airborne acoustical noise emissions [dB(A) re 1 pW] | 39 |
| Airborne acoustical noise emission class | / |
| Minimum ambient temperature for which the refrigerating appliance is suitable | 16 |
| Maximum ambient temperature for which the refrigerating appliance is suitable | 38 |
| Winter setting | No |
| Number of doors or compartments (whichever is lower) | 1 |
| Fast freeze facility (for 4-star compartments) | No |
| Type of light source | - |
| Energy efficiency class - light source | / |
| COMPARTMENT 1 PARAMETERS | |
| Compartment type | Fresh Food |
| Compartment volume | 47 |
| Recommended temperature setting for optimised food storage | 4 |
| Freezing capacity | - |
| Defrosting type | Auto |
| Target temperature (Tc) | 4 |
| Thermodynamic parameter (rc) | / |
| Modelling parameter (Nc) | / |
| Modelling parameter (Mc) | / |
| Defrost factor (Ac) | / |
| Built-in factor (Bc) | / |
| COMPARTMENT 2 PARAMETERS | |
| Compartment type | / |
| Compartment volume | / |
| Recommended temperature setting for optimised food storage | / |
| Freezing capacity | / |

| | |
|--------------------------------|-----|
| Defrosting type | / |
| Target temperature (Tc) | / |
| Thermodynamic parameter (rc) | / |
| Modelling parameter (Nc) | / |
| Modelling parameter (Mc) | / |
| Defrost factor (Ac) | / |
| Built-in factor (Bc) | / |
| LOGISTIC DATA | |
| Net height (mm) | 522 |
| Net width (mm) | 479 |
| Net depth with handle (mm) | 447 |
| Gross height (mm) | 535 |
| Gross width (mm) | 515 |
| Gross depth (mm) | 465 |
| Gross volume (m ³) | / |
| Net weight (kg) | 16 |
| Gross weight (kg) | 18 |